

Roller Block up to 1200 kg - TR-1200

Advantages of the modular system

With our TR 1200 small containers and pipes can be positioned easily and circular weld seams can be welded. Due to its low start-up costs the purchase of the TR 1200 will pay off soon. By means of a torch holder, the welding process can be further simplified and the welder can concentrate exclusively on the control of the welding process.





Roller Block up to 1200 kg - TR-1200



Features

- Device for turning and positioning containers and cylindrical workpieces.
- Unit in solid steel construction with PU-coated metal rollers.
- Precise speed adjustment via frequency inverter.
- Foot switch for start/stop, 4-cyle operation.
- Switch for cw/ccw rotation.
- Turning knob for infinitely adjustable rotational speed.
- Changeover switch for quick/normal operation.
- Switch with control lamp for readiness for operation.
- HF-protected.



Scope of delivery: 1 Control unit (integrated)

1 Foot switch

Model	TR-1200 complete
Supply voltage	230 V 50/60 Hz
Power fuse	10 Amp
Load capacity	1.200 kg
Speed	80 - 1.600 mm/min.
Roller diameter	200 mm
Roller width	50 mm
Workpiece diameter	20 – 800 mm
Measurem. $(LxWxH)$ mm	520 x 470 x 390
Total weight	56 kg
Item no.	71821150

Model	TR-1200 Idler roller
Load capacity	600 kg
Roller diameter	200 mm
Roller width	50 mm
Workpiece diameter	20 – 800 mm
Weight	17 kg
Measurements $(LxWxH)$ mm	450 x 160 x 340
Item no.	71821150.0010